TECHNICAL DATASHEET 2011-582

SPL 351 ANTISLIP TC HEAVY

SPL35121

Date	2/10/2017					
Backing	100% Polyester					
<u>Coating</u>	100% PVC					
Composition	Coating		340	g/m²		
<u>F + + + + + + + + + + + + + + + + + + +</u>	Backing		50	g/m²		
	Lacquer		5	g/m²		
	Total		395	g/m²	± 20 g/m²	
Tensile strength	ISO 1421 : 1998	length	>25	daN/ 5 cm		
- renone ou ongen	100 1421 1000	width	>15	daN/ 5 cm		
Tear strength	ISO 4674-01 : 2003	length	>1,5	daN		
		width	>1,5	daN		
Seam resistance	ISO 13935-1 : 2014	•	>10	daN/ 5cm		
		width	>10	daN/ 5cm		
% Elemention under 20N/Fem	100 1 401 - 4009	longth	\ <i>F</i>	0/		
<u>% Elongation under 30N/5cm</u>	ISO 1421 : 1998	length width	>5 >5	%		
		width	>0	70		
Coating to fabric adhesion	ISO 2411 : 2000		>2,5	daN/ 5cm		
Flex resistance	ISO 5402 1 : 2003		no qualit	y loss after 20	200000	
Hydrostatic head	ISO 1420 : 1978		>200 cm Tight to h	nouse dust m	nites	
Cleaning We recommend to clean this article with wa damage this product. Disinfecting On request a list of approved disinfectants				Ū	iol, solvent, bleach or abrasive products can	
			responsat	inty for dama	age il other products are used.	
<u>Care</u>	ISO/FDIS 3758 : 200	15				
40	*	×		\otimes	\boxtimes	
Shrinkage after washing: Alcohol in high concentrations might dama	< 3% ge this article.					



<u>Other</u>

This article is HF weldable, this should however be tested on your equipment. This article has non-skid properties.

Remarks

All the specifications given in this document have been tested in accredited laboratories or in our own laboratory using officially calibrated measuring equipment.

This datasheet is valid for five years after the date of publication. However, we guarantee that the item has been produced with the same ingredients and ISO-9000 procedures were strictly complied with. In the event that any modifications may have been applied during this period, all the properties were retested.

The items delivered comply with the specifications stated in this datasheet. In principle, we do not guarantee properties or characteristics that are not included in it.

Slight colour variations between deliveries are possible. We recommend that you always process items from different deliveries separately. This item complies with the most recent REACH specifications.

APPROVAL : CEO

